



# UTIFORM

---

## Plastering Machines \_ Screed Pumps

*Utiform UK*

## Utiform Master Plastering Machine

[Call for Pricing](#)

Utiform Master Plastering Machine Characteristics

- Three phase mixing pump for interior and exterior coatings (gypsum, mortar, render)
- Simple and robust.
- Can be filled with premixed material from bags or from silos.
- Horizontal material feeding, avoiding desegregation of materials.
- The pump transports the mix through hoses to the spray gun, where with help of compressed air, the material is sprayed on the surface.
- Cylindrical mixing tube with "guillotine" closing system.
- Special designed electric box with automatic shut off system for pump and compressor.
- Holders for accesories and tools.
- In case of loss of water pressure the machine is switched off automatically.
- Sealed electric box to avoid damage by dust or water.
- The correct turning direction is guaranteed by a two direction switch on the electric board.
- Perfect water dosification and regulation with flow meter to guarantee continous mix.
- For special applications the machine can be equipped with a cable remote control.
- Easy to use due to ergonomic design.
- Easy to clean and maintain.
- For easy transportation between floors on site the machine can be taken to parts within minutes.
- Big toolbox for tools.
- Machine with 4 wheels for easy transport on site.
- Low filling height.

Standard equipment:

- Automatic shut off system.
- Compressor 250 l/min.
- Water Pump.
- Tool and Cleaning Kit.
- Spray Gun.
- Mixing shaft.
- Warranty Certificate.
- CE Certificate.
- Parts book and manual.
- Tool Kit (spanners).

Recommended equipment:

- Stator / Rotor.
- 10 m mortar hose Dn 25 mm.
- 10 m air hose 3/8"
- 5 m water hose 3/4" + suction valve
- 25 m electric cable 5x2'5 mm<sup>2</sup>

Technical data :

Conveying output	5 to 30 l/min
Pumping distance	approx. 40 m
Pumping height	approx. 20 m
Pumping pressure	30 bars max.

Power of mixing motor	5.5 Kw
Power of feed motor	1.1 Kw
Air compressor	250 l/min, 5 bar, 0.9 Kw
Water pressure required	3 bars
Electrical connection (5x2,5mm <sup>2</sup> )	400 V-50Hz 3 P+N+T 32A/6h
Size LxWxH (mm)	1.420 x 660 x 1.540
Loading height	1.010 mm
Tank capacity	130 l approx.

### [Vendor Information](#)

**Customer Reviews:** There are yet no reviews for this product.  
Please log in to write a review.