



UTIFORM

Plastering Machines _ Screed Pumps

Utiform UK

Utiform Vario Plastering Machine

[Call for Pricing](#)

Utiform Vario Plastering Machine Characteristics

- Electric mortar pump.
- For the continuous pumping of material up to 6 mm grain size.
- Robust and easy maintenance.
- High performance stator / rotor pump.
- Maintenance free motor and gearbox (380 V/50 Hz).
- Material hopper with 80 liters capacity and low filling height.
- Chassis mounted on 2 wheels for easy transport.
- For special application with options of pneumatic or electric remote control system.
- High performance mortar pump for pumping, spraying and injecting all sorts of mortars.
- Simple and robust.
- Easy to use.
- Multiple applications.

Standard equipment:

- Chassis with protection hood for motor.
- Hopper with grill (incl. safety system)
- Motor and gearbox.
- Stator + Rotor.
- Material outlet 50 mm.
- Electric control box. 3P+N+T 32 A/6h, plug for mixers, compressor and forward - backward switch.
- Tool kit and cleaning tools.
- Warranty certificate.
- CE certificate.
- Instructions manual and parts book.

Recommended equipment:

- 25m electric cable 5 x 2,5 mm²
- Spray gun.
- 2 x 15 m mortar hose 35 mm.
- 2 x 15 m air hose.
- Spraying kit.

Technical data :

	E	EV (variator)	230 V.
Electrical connection	400 V / 50 Hz	400 V / 50 Hz	230 V / 50 Hz
Power of electric motor	4,8 - 6,0 Kw	5,5 Kw	4 Kw
Grain size* 2L6	0 a 4 - 6 mm	0 a 4 - 6 mm	0 a 4 - 6 mm
Maximum working pressure	10 a 30 bar	10 a 30 bar	10 a 30 bar
Theoretical power range	20 - 45 l/min	5 - 40 l/min	20 - 45 l/min
Loading height (without vibrating sieve)	550 mm	550 mm	550 mm

[Vendor Information](#)

Customer Reviews: There are yet no reviews for this product.
Please log in to write a review.