



# UTIFORM

---

## Plastering Machines \_ Screed Pumps

*Utiform UK*

### Utiform V2 Plastering Machine

[Call for Pricing](#)

#### **Utiform V2 Plastering Machine Characteristics**

- Rendering machine for one coat render, traditional mortar and all sorts of premixed mortar.
- Ideal for cement based renders, one coat renders, repair mortars and traditional mortars.
- Forward - Backward drive of the pump for easy cleaning and avoid material blockages.
- Large radiator with cooling unit to avoid heating of the motor and hydraulics.
- Three cylinder 21 HP water cooled engine for best performance even in difficult circumstances. Low noise level and low consumption.
- The pneumatic remote control at the spray gun, that stops the pump and lowers the revolutions of the motor makes the machine even more comfortable.
- Max. grain size 6mm.
- Equipped with stator and rotor 2L6 with an output up to 3,6 m<sup>3</sup>/h.
- Can be used for small quantities of self levelling floor material.
- Excelent towing performance due to low gravity point.
- The serial remote control allows to start and stop the machine from any point during the working process.
- Uniform spray due to 375 l/min two cylinder compressor.

Standard equipment:

- Towable.
- Air compressor 375 l/6 bar.
- Stator + Rotor.
- Electric control panel.
- Tools and cleaning kit.
- Warranty certificate.
- CE certificate.
- Instructions manual and partsbook.

Recommended equipment:

- 2 x 15 m mortar hose 35 mm
- 1 x 5 m mortar hose 25 mm
- 1 x 15 m air hose.
- 1 x 20 m air hose.
- Spray gun.

Technical data :

Motor	Diesel	Electrical
Plaster conveying capacity	0-60 l/min *	0-60 l/min *
Max. grain size	2L6 - 6 mm Triple plus- 8 mm	2L6 - 6 mm Triple plus- 8 mm
Conveying height	40-50 m	40-50 m
Conveying distance	80-100 m	80-100 m
Weight	750 Kg	750 Kg
Size LxWxH (mm)	3300 x 1150 x 1200	3300 x 1150 x 1200

[Vendor Information](#)

**Customer Reviews:** There are yet no reviews for this product.  
Please log in to write a review.